



KRATOS HELIXON-S WIRE ROPE RETRACTABLE FALL ARREST

SKU: N/A

From £357.57 ex VAT

Stock: Available to Order (2-3 Days) Ordered in and delivered within 2-3 days.

SKU	Stock Status	Stock Quantity	Length	Price
FA2040210	Available to Order (2-3 Days) Ordered in and delivered within 2-3 days.		10.0m	£357.57 ex VAT
FA2040215	Available to Order (2-3 Days) Ordered in and delivered within 2-3 days.		15.0m	£437.46 ex VAT
FA2040220	Out of stock Currently unavailable. This item will be delivered when stock arrives.	0	20.0m	£497.22 ex VAT

Robust & durable polymer casing, equipped with:

a carrying handle,
a wire rope-cleaning brush,
a window, that can be easily removed for reaching the internal mechanism, in order to inspect it without totally opening the casing.

Comes with Galvanized Steel Wire Rope of diam 4.8 mm, having:

a connector ref. FA 50 203 20 with load indicator,
a gripping handle,
an external energy absorber.

- Internal braking mechanism to reduce the fall arrest force to less than 6 kN.
- Swivel and FA 50 101 17 connector at anchorage end.

Compliance: EN 360:2002.

Minimum breaking strength > 12 kN.

Approved for a user with a max. weight of 140 kg in vertical use and in horizontal use.

HS Code: 8428 9090

Delivered with a cord (FA 20 904 15) for guiding the winding back of the wire rope.