



KRATOS LIFT RES-Q EVACUATION & RESCUE DEVICE 40M

SKU: FA7020140

£1,319.40 ex VAT

Stock: Available to Order (3-5 Days) Ordered in and delivered within 3-5 days.

Lift Res-Q is the perfect device for lifting and rescue operations.

Made of aluminium alloy and high-strength steel and dia. 9.6 mm semi-static kernmantle rope assembled with the device.

Rope ends with double figure of 8 knots for connection with karabiner. Provided with 2 hooks ref. FA 50 220 21.

Controlled descent speed: 1 m to 1.5 m / sec (depending on weight), up to 225 kg.

Maximum descent height: 500 m.

Maximum lifting height: 500 m.

Usable with electric screwdriver: For high ascents.

Brake system: Automatic and redundant.

Maximum no. of users: 2 users - 225 kg.

Inspection: Once a year or every 6000 m of rope.

Available in 2 lengths: 20 m (FA 70 201 20), 40 m (FA 70 201 40).

For specific lengths, you need to associate the following references:

- FA 70 201 00: device only.
- FA 70 109 99: Kernmantle rope per meter.
- FA 70 109 98: Required length of rope with double "figure of 8" knots and automatic locking hook.

Compliance: EN 341:2011-1A, EN 1496:2007 B, EN 12841:2006 Type C (1 person).

KRATOS SAFETY Lift Res-Q (BKLKT101-09)_new version_web [Download](#)

